



- Designed for industrial and commercial filter applications
- Heavy duty construction for maximum durability
- Various materials of construction for a wide range of process requirements

316L stainless steel  
304L stainless steel

- Accepts Double Open End (DOE) cartridges
- Available with 1" in-line connections for easy installation.
- Ring nut closure for quick cartridge change outs
- Spring loaded knife edge seal provides positive sealing for variable length cartridges
- Supplied with mounting bracket kit and wrench
- Numerous gasket options for compatibility with most fluids
- Flat top available for 1/4" gauge ports options

### Applications

Water

Food & Beverage

Oil

Coolants

Chemicals

Electronics

Inks / Paints / Coatings

Pulp & Paper

## Specifications & Operating Parameters

### Maximum Operating Pressure

300 psig (20.7 bar) @ 200° F (93° C)

### Connections

Inlet /Outlet: 1" FNPT

Optional: BSP

Drain: V – 1/4" NPT Plug

T – 1/4" NPT Petcock

### Materials of Construction

Head / Shell: S6 316L SS / 316L SS

S4 304L SS/ 304L SS

Drain: V – SS Plug

T – Brass Petcock

### Gaskets

Buna N (FDA Grade)

Optional: EPDM, Silicone, Viton

### Cartridge Type

DOE Cartridges

### Custom Options

– Gauge Ports

See Ordering Guide for complete selection of options